

## ENERFLEET SAE 50

### DESCRIPTION:

A monograde oil for diesel and gasoline engines. Formulated with highly refined mineral bases and additives with excellent detergent, anti-wear, dispersant and anti-corrosive properties.

### PROPERTIES:

- ✓ Prolonged service life.
- ✓ Excellent resistance to oxidation, minimal thermal and chemical degradation.
- ✓ High protection against the wear of lubricated elements.
- ✓ Excellent detergent and dispersant properties, thereby preventing the formation of sludge when cold, stuck parts, blocked and silted filters.
- ✓ Minimal formation of deposits, keeping the lubricated elements in an optimum state of cleanliness.
- ✓ High TBN value, ideal for the control of acids formed during the combustion of diesel fuel with a high sulphur content.

### APPLICATIONS:

- ✓ High-speed medium gasoline and diesel marine engines in pleasure boats, fishing fleets and in general in engines that work with fuels with low sulfur content.
- ✓ Mixed fleets of diesel engine vehicles requiring an API CF level of quality.
- ✓ Industrial vehicles, trucks, vans and agriculture machinery, fishing fleets.
- ✓ Naturally aspirated and/or supercharged diesel engines subjected to severe workloads.
- ✓ Cranes, command and control systems, civil engineering equipment gears.
- ✓ Petrol engines with or without a catalyst.

### SPECIFICATIONS:

API	CCMC
CAT	ALLISON

### DONNÉES TECHNIQUES:

PHYSICAL & CHEMICAL CHARACTERISTICS	STANDARD	VALUE
SAE grade	SAE J300	50
Viscosity at 100°C (Cst), typical	ASTM D-445	16,3 – 21,9
Density at 15°C, Typical (kg/l)	ASTM D-1298	0,9
Pour point (°C)	ASTM D-97	< -9
Flash point (°C)	ASTM D-92	200
TBN (mg KOH/g), typical	ASTM D-2896	8

### PACKAGING:

20L jerrycan, 200L drum and 1000L IBC container.

**ENERMIN INTERNATIONAL SA**  
Secteur 24, ZAD II, Lot 7,  
Parcelle 9, section 114  
01 BP 3138 OUAGADOUGOU 01  
BURKINA FASO  
Tel: +226 25418212  
[www.enermin-international.com](http://www.enermin-international.com)